

23010 Ryen Dr NW, Ste C. • Poulsbo, WA 98370-6406 (360) 598-3090 • FAX (206) 494-7787 email: info@tarpinnovators.com

PRODUCT SPECIFICATIONS

61" 40oz VINYL FR PVC Coated Polyester TI P/N: VI-40-061-50-FR

Width	61 inches
Base Fabric (100% Polyester)	1500D x 1500D / 26 x 27
Weight (FS-191-5041)	40 oz / yard ²
Tensile Strength (Grab) (FS-191-5100)	960 lbs x 920 lbs
Tensile Strength (Strip) (FS-191-5102)	685 lbs x 655 lbs
Tear Strength (Tongue) (FS-191-5134)	380 lbs x 390 lbs
Adhesion Strength (FS-191-5970)	14 x 11 lbs / inch
Abrasion Resistance (FS-191-5306)	715 cycles
Hydrostatic Resistance (FS-191-5512)	At least 600 lbs / inch ²
U.V. Resistance (Weather-O-Meter)	Not excessive fading after 300 HRS
Cold Crack Resistance (FS-191-5874)	-40° F
High Temperature Resistance (FS-191-5872)	180° F (Does not Block)
Flame Resistance	NFPA 701
Special Treatment(s)	Acrylic Lacquer (Both Sides) Non-Skid Embossing (Face Side)

This information is offered for your general guidance only. Above values represent typical data and are subject to slight variations. It is accurate to the best of our knowledge at the time of printing but is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to safe handling of this material. No warranty is expressed or implied regarding the accuracy of these data.